



www.vcom.com.hk

VCOM INTERNATIONAL LTD.

Head Quarter

#12F, Building B, Yuhua Business Center, Wuxi Rd, Tangzhu, Tianjin District,
Guangzhou City, Guangdong Province, China
Tel: +86-20-89529620 Fax: +86-20-89529620 Email: vcom@vcom.hk

Cable & Electronics Factory

#Guangming Industrial Zone, Longmen Town, Beikou District, Huizhou City,
Guangdong Province, China
Tel: +86-752-8871121 Fax: +86-752-8871133

VCOM
CABLE & ELECTRONICS



**TO BE THE GLOBAL NO.1
BRAND ON COMPUTER PERIPHERALS**

www.vcom.com.hk

COMPANY PROFILE

VCOM INTERNATIONAL LTD is one of the subsidiaries of VCOM Group. It was founded in 2004, located in Guangzhou China. It is professional in intelligent building calling system. We are a collaboration enterprise with R&D, sales and service. We have three production bases, which are located in Dongguan, Huizhou and Fuzhou Zhangpu.

We have independent intellectual property rights of VCOM brand. After years of continuous development and innovation, VCOM has become integrated cable industry recognized as the most valuable international brand. VCOM has high reputation in domestic and abroad. We have branches, agents in major cities in China, and have agents in more than 70 countries in the world. Relying on powerful R&D team and production technology, we have developed Cat5e/UTP/FTP/SFTP and Cat6 systems, Cat7 cabling system, coaxial CCTV system, telephone voice system, audio and video teaching system and so on. The SFTP Cat6 cable structure has obtained China national practical patent. VCOM has passed the international ISO9001 (2008) quality system certificate, our products passed the UL, CE, VDE certificates and China 3C certification.

VCOM takes the concept of win-win cooperation, continues to expand and deepen the business channels. We set up branches or agents not only in China but in all over the world. We established a perfect sales and after-sales service system, to promote VCOM brand growth. With stable quality and good reputation, excellent market achievements for successive years, VCOM has all kinds of industry users and supports. VCOM cabling system products have been widely used in the financial, medical, university, airports, sea ports and train stations and other various of industries project.

VCOM International LTD will do more detailed market analysis and surveys to develop more user-friendly products and solutions. We are continuously to make contribution to the development of industry by our own efforts.



CONTENTS

1.Audio

1.1 Children Headphone.....	05
1.2 Headphone.....	07
1.3 Bluetooth Headphone.....	09
1.4 Bluetooth Speaker.....	11

2.Computer Accessory

2.1 Mouse.....	13
2.2 Vertical Mouse.....	15
2.3 Keyboard.....	17
2.4 Mouse & Keyboard Combo.....	17
2.5 USB HUB.....	19
2.6 Webcam.....	20

3.Chargers

3.1 Wall-Charger.....	21
3.2 USB Desktop Charger.....	22
3.3 Car Charger.....	22

4.AV Adaptor

4.1 HDMI Splitter.....	25
4.2 HDMI Switch.....	24
4.3 HDMI Switch.....	26
4.4 VGA Splitter.....	26
4.5 Extender.....	28



PC PERIPHERAL ELECTRONICS



Beyond your imagination


PRINCESS Series



DE801



HERO Series



DE803



MONSTER Series



DE802



MONSTER Series



DE805



Children Headphone



Children Headphones
Driver(s): 32mm
Impedance: 32Ω
Sensitivity: 100dB (at 1kHz/1kHz)
Frequency Response: 20Hz-20kHz
Max Input Power: 100mW
Length of Cord: 1.5m
Plug Type: 3.5mm stereo-plug with or without an optional



DEBQ-41
Children: ReadyPhone
Silver/Land: Silver
Impedance: 32Ω
Sensitivity: 85±5dB at 1kHz/1kHz
Frequency Response: 20Hz-20kHz
Max Input Power: 10mW
Length of Cord: 1.0m
Plug Type: 3.5mm stereo plug with
or without an optional



Children's Headphones
(Over 100) \$100
Importance: 500
Sensitivity: 125,000 (100,000) 1000
Frequency Response: 2000-20000
Max Input Power: 100mW
Length of Cord: 1.5m
Plug Type: 3.5mm stereo plug with
or without ear control



DEMS-4
Children Headphone
Driver (x4): 30mm
Impedance: 30Ω
Sensitivity: 95dB/m (at 1kHz/100mV)
Frequency Response: 20Hz-20KHz
Max Input Power: 100mW
Length of Cord: 1.5m
Plug Type: 3.5mm stereo plug with
or without ear cord



DEHP-2
Children's Headphones
Driver Unit: 30mm
Impedance: 32Ω
Sensitivity: Very difficult to hear (normal)
Frequency Response: 20Hz-20KHz
Max Input Power: 200mW
Length of Cord: 1.5m
Plug Type: 3.5mm stereo plug with or without mic optional



QEM2-Y
Children's Headphone
 Driver Unit: 30mm
 Impedance: 32Ω
 Sensitivity: 95dB/mW at 1kHz
 Frequency Response: 20Hz-20kHz
 Max Input Power: 300mW
 Length of Cord: 1.5m
 Plug Type: 3.5mm stereo plug with
 an in-line on/off switch



DE902-PB
Children Headphone
Driver Unit: 30mm
Impedance: 32Ω
Sensitivity: 100dB (at 1kHz/100mW)
Frequency Response: 20Hz-20kHz
Max Input Power: 100mW
Length of Cord: 1.5m
Plug Type: 3.5mm stereo plug with or without the optional



DE803-YB
Children: Handphone
Color LCD Screen
Impedance: 32Ω
Sensitivity: 100mV (at 1kHz/100Hz)
Frequency Response: 20Hz-20kHz
S/N Ratio: 90dB
Length of Cord: 1.5m
Plug type: 3.5mm stereo plug with or without mic optional



CHILD-AL1
Children's Headphone
Driver: 40mm, 30mm
Impedance: 32Ω
Sensitivity: 100dB (at 1mW/1kHz)
Frequency Response: 20Hz-20kHz
Max Input Power: 100mW
Length of Cord: 1.5m
Plug Type: 3.5mm stereo plug with
a without the adapter



DEANS-PILZ
Elektronik Messtechnik
 Group Ltd. 60mm
 Impedance: 500
 Sensitivity: 10mV/g (at 100Hz/Hz)
 Frequency Response: 20Hz-200Hz
 Max Input Power: 30mW
 Length: 150mm
 Plug Type: 3.5mm stereo plug with
 1/8" (3.175mm) diameter



CD-DA3-AM-1
MiniDisc Headphones
 Driver Unit: 32mm
 Impedance: 320
 Sensitivity: 100dB (1mW/1kHz)
 Frequency Response: 20Hz-20kHz
 Max Input Power: 300mW
 Length of Cord: 1.5m
 Plug Type: 3.5mm stereo plug with
 earhook and ear cushion



DEBOS-PW
Chlorine Disinfectant
 Gross Unit: 30mm
 Impurities: 100
 Sensitivity: 100 (at 1000000)
 Frequency/Response: 1000/10000
 Max Input/Power: 1000W
 Length of Cord: 1.5m
 Plug Type: 30mm stereo plug with
 or without an internal



EXIBOS-PHY
Einblende-Wechselplatte
 Grösse: 100 x 100 mm
 Kapazität: 3000
 Sensitivität: 100000 (per horizontal)
 Frequenz-Response: 20Hz-20KHz
 Max-Input-Power: 10Watt
 Length of Lead: 1 m



DEMO-NY
 Address: The telephone
 Group: Unit: 1000
 Importance: 100
 Security: 100
 Frequency: 100
 Length of time: 100



D6834
 Divergent: 2000
 Divergent: 2000
 Divergent: 2000
 Divergent: 2000
 Divergent: 2000
 Divergent: 2000



CRB17
Strong Monthly Review
 Positive Price Impact
 Strong gains since
 September 2011
 Reversing 2008-2009 period losses
 Prospects bright, strong earnings
 Good sample of data



CHIEF
Group Headquarters
 10000 Hwy 100
 Suite 100
 Houston, TX 77036
 Telephone: 713/865-1111
 Fax: 713/865-1111



Headphone

PC Headphone

DE160

Driver Unit: 40mm
Impedance: 32Ω
Sensitivity: 108±3dB (at 1mW/1000μ)
Frequency Response: 20Hz-20KHz
Max Input Power: 100mW
Length of Cord: 2.1m
Plug Type: 3.5mm



DE149U

Driver Unit: 40mm
Impedance: 32Ω
Sensitivity: 110±3dB (at 1mW/1000μ)
Frequency Response: 20Hz-20KHz
Max Input Power: 100mW
Length of Cord: 3m
Plug Type: USB port



Mobile Headphone

DE168M

Driver Unit: 40mm
Impedance: 32Ω
Sensitivity: 108±3dB (at 1mW/1000μ)
Frequency Response: 20Hz-20KHz
Max Input Power: 100mW
Length of Cord: 1.8m
Plug Type: 3.5mm



USB Headphone

DE168U

Driver Unit: 40mm
Impedance: 32Ω
Sensitivity: 108±3dB (at 1mW/1000μ)
Frequency Response: 20Hz-20KHz
Max Input Power: 100mW
Length of Cord: 1.8m
Plug Type: USB port



Bluetooth Headphone

M290

Bluetooth version: V5.0+EDR
Transmission distance: 10 m
Playing time: 4 hours
Standby time: 300 hours
Battery: 200mAh-rechargeable lithium battery
Charging time: 1.5 hours



M292

Bluetooth version: V5.0+EDR
Transmission distance: 10 m
Standby time: 300 hours
Battery: 200mAh-rechargeable lithium battery
Charging time: 1.5 hours



M291

Bluetooth version: V5.0+EDR
Transmission distance: 10 m
Standby time: 300 hours
Battery: 200mAh-rechargeable lithium battery
Charging time: 1.5 hours



M293

Bluetooth version: V5.0+EDR
Transmission distance: 10 m
Standby time: 300 hours
Battery: 200mAh-rechargeable lithium battery
Charging time: 1.5 hours



M277

Bluetooth version: V5.0+EDR
Transmission distance: 10 m
Battery: 300mAh-rechargeable lithium battery
Charging time: 2 hours
Music playing time: 10 hours



M256

Bluetooth version: V5.0+EDR
Battery: 200mAh-rechargeable lithium battery
Charging time: 1 hour
Music playback time: 3-4 hours



Active Noise Cancellation Bluetooth Headphone



M292IANC

Chipset: JL
Bluetooth version: V5.0+EDR
Battery: 200mAh rechargeable lithium battery
Playing time (Noise reduction + Bluetooth): 30 hours



M293IANC

Chipset: JL
Bluetooth version: V5.0+EDR
Battery: 200mAh rechargeable lithium battery
Playing time (Noise reduction + Bluetooth): 30 hours

New Arrival ANC Headphone



Built for Comfort

Active Noise Cancelling

Professional Active Noise Cancelling Technology.
Significant noise reduction for travel, work and anywhere in between.

ACTIVE NOISE CANCELLING /

ANC

Hi-Fi



M293IANC

Chipset: CSR8635
Wireless version: V4.1
Battery capacity: 600mAh rechargeable lithium battery
Playing time: 18 hours



600mAh
Rechargeable Battery



Independent
ANC Switch



Hands-free
Calling



18h
Playing Time

Bluetooth Speaker



M306

Bluetooth Version: 4.2
MAX Power Output: 3W*2
Battery: 1200mAh
Music Playback Time: 4 hours



AUX

TF Card Play

FM Stereo Radio

U-Disk



M301

Bluetooth Version: 4.2
MAX Power Output: 5W*2
Battery: 1200mAh
Charging Time: 3 hours
Music Playback Time: 4 hours



AUX

TF Card Play

FM Stereo Radio

U-Disk

M302

Bluetooth Version: 5.0
MAX Power Output: 5W*2
Battery: 1200mAh
Music Playback Time: 4 hours



AUX

TF Card Play

FM Stereo Radio

U-Disk



M307

Bluetooth Version: 5.0
MAX Power Output: 5W*2
Battery: 1200mAh
Music Playback Time: 4 hours



AUX

TF Card Play

FM Stereo Radio

U-Disk



M332

Bluetooth Version: 4.1
MAX Power Output: 5W*2
Battery: 1200mAh
Music Playback Time: 4 hours



AUX

TF Card Play

FM Stereo Radio

U-Disk



M309

Bluetooth Version: 4.2
MAX Power Output: 3W
Battery: 450mAh
Music Playback Time: 3 hours



AUX

TF Card Play

FM Stereo Radio

U-Disk

M330

Bluetooth Version: 4.1
MAX Power Output: 5W*2
Battery: 1200mAh
Music Playback Time: 4 hours



AUX

TF Card Play

FM Stereo Radio

U-Disk



M331

Bluetooth Version: 4.1
MAX Power Output: 5W
Battery: 1200mAh
Music Playback Time: 4 hours



AUX

TF Card Play

FM Stereo Radio

U-Disk



MOUSE

Wired Mouse

DM106

Wired Mouse
Material: ABS
Resolution: 800/1200/1200 DPI
Key Number: 3
Key life: 1000000 times
Interface: USB
Cable Length: 1.20m



DM114

Wired Mouse
Material: ABS
Resolution: 1200 DPI
Key Number: 3
Key life: 1000000 times
System Requirement: Windows98/2000/XP
/ Vista/7/8/10/ MAC OS X



DM115

Wired Mouse
Material: ABS
Resolution: 1000 DPI
Key Number: 3
Key life: 2000000 times
System Requirement: Windows98/2000/XP
/ Vista/7/8/10/ MAC OS X



Wireless Mouse

DM554

Bluetooth Mouse
Working Frequency: 2.4GHz
Working Distance: 10m
Resolution: 800/1600/1600 DPI
Key Number: 6
Key life: 2000000 times
Battery Requirement: AAA/batteries
System Requirement: Windows2000/XP
/ Vista/7/8/10/ MAC OS



DM555

Wireless Mouse
Material: ABS
Resolution: 1000/1200/1600 DPI
Key Number: 6
Working Frequency: 2.4GHz
Working Distance: 10m
Key life: 1000000 times
Battery Requirement: 2*AAA batteries
System Requirement: Windows98/2000/XP/7/8/10/XP/ Vista/7/8/10/ MAC OS
Grey, Black, Red, Blue



DM558

Bluetooth Mouse
Working Frequency: 2.4GHz
Working Distance: 10m
Resolution: 800/1200/1600 DPI
Key Number: 6
Key life: 1000000 times
Battery: AAA (not included)
System Requirement: Windows98/2000/XP/7/8/10/XP/ Vista/7/8/10/ MAC OS



DM559

Working Frequency: 2.4GHz
Working Distance: 10m
Resolution: 1200 DPI
Key Number: 3
Key life: 1000000 times
Battery: AAA (not included)
System Requirement: Windows98/2000/XP/7/8/10/XP/ Vista/7/8/10/ MAC OS



DM529C

Bluetooth Two-Port Mouse
Resolution: 800/1200/1600 DPI
Key Number: 4
Key life: 1000000 times
Interface: USB/Type-c receiver
System Requirement: Windows98/2000/XP/7/8/10/XP/ Vista/7/8/10/ MAC OS
Battery: AAA (not included)



Wired GAME MOUSE

DM426

Material: ABS
Resolution: 800/1200/1600/2000
/1400 DPI
Key Number: 6
Key life: 1000000 times
Interface: USB or PS/2 Optional
System Requirement: Windows98/2000/XP/7/8/10/XP/ Vista/7/8/10/ MAC OS



DM421

Material: ABS
Resolution: 800/1200/1600/2000
/1400 DPI
Key Number: 6
Key life: 1000000 times
Interface: USB or PS/2 Optional
System Requirement: Windows98/2000/XP/7/8/10/XP/ Vista/7/8/10/ MAC OS



DM418

Game Mouse
8D design with DPI button and forward
backward button
Connection: Wired/USB/2 interface
Resolution: 800/1200/1600/2000 DPI
Working environment: 0-100°C
Key life: 1000000 times
Suitable for: Windows2000/XP/Vista/7/8/10/ MAC OS



DM419

Game Mouse
8D design with DPI button and forward
backward button
Connection: Wired/USB/2 interface
Resolution: 800/1200/1600/2000 DPI
Working environment: 0-100°C
Key life: 1000000 times
Suitable for: Windows2000/XP/Vista/7/8/10/ MAC OS



Wireless GAME MOUSE

DM601

Material: ABS
Working Frequency: 2.4GHz
Working Distance: 10m
Resolution: 800/1200/1600/2000/1400 DPI
Key Number: 3
Key life: 1000000 times
Battery: AAA/2 (not included)
System Requirement: Windows98/2000/XP/7/8/10/XP/ Vista/7/8/10/ MAC OS



DM602

Material: ABS
Working Frequency: 2.4GHz
Working Distance: 10m
Resolution: 800/1200/1600/2000/1400 DPI
Key Number: 3
Key life: 1000000 times
Battery: AAA/2 (not included)
System Requirement: Windows98/2000/XP/7/8/10/XP/ Vista/7/8/10/ MAC OS



DM553

Material: ABS
Working Frequency: 2.4GHz
Working Distance: 10M
Resolution: 800/1000/1600/2000/2400 DPI
Key Function: 5
Key life: 3000000 times
Battery: AA/1 (not included)
System Requirement: Windows®8/2000/7/8
/10(Mac/Unix/Linux)



DM531

Material: ABS
Working Frequency: 2.4GHz
Working Distance: 10M
Resolution: 800/1000/1600/2000/2400 DPI
Key Function: 7
Key life: 3000000 times
Battery: AAA/3 (not included)
System Requirement: Windows®8/2000/7/8
/10(Mac/Unix/Linux)



Vertical Mouse ➡

DM430

Vertical Mouse

1. 2.4G-BT+RF2.4, dual-mode
2. This charging interface is Type-C, the 2.4G Bluetooth receiver is a USB-A interface, and the mouse must be equipped with an A2C charging cable;
3. RGB colored lights;
4. DPI: 1000/1600 (default)/2400DPI
5. Battery capacity: 1500mAh
6. System Requirements: Windows 10/Mac/2000/XP/Vista/7/Win7/Win8/Win10 or the latest version.



VERTICAL MOUSE

DM430



Ergonomic Design



Smart Information

Born for health!



System requirements :

Windows 10/8/2000/XP/Vista/ Win7 /Win8/ Win10 or the latest version.

Dual-Mode
2.4G+BT



Type C Interface



DPI:
1000/1600/2400



RGB
Colored Lights



Battery Capacity:
1500mAh



Keyboard

Waterproof Keyboard Standard Keyboard Multimedia Keyboard Ultra Slim Multimedia Keyboard

DK601

Multimedia Keyboard

Material: ABS plastic
Key switch: Membrane/Keyswitch
Keycaps type: printing
Key stroke life: 10 million times
Key layout: 104+10keys



DK791

Water Proof Keyboard

Material: ABS plastic
Key switch: Membrane/Keyswitch
Keycaps type: printing
Key stroke life: 10 million times
Key layout: 107 keys



DK123

Wired Keyboard

Material: ABS
Key layout: 104 keys
Key stroke life: 10 million times
System Requirement:
Windows 98/2000/XP/10/11/12/13/14/15/16/17/18/19/20



Mouse & Keyboard Combo

DK204

2.4G Wireless Waterproof Keyboard & Mouse

Mouse:
Working Frequency: 2.4GHz
Working Distance: 5m
Resolution: 800/1200/1600 DPI
Key Number: 3
Key life: 2000000 times
Battery Requirement: AA*1 batteries

Keyboard:
Working Frequency: 2.4GHz
Key layout: 104 keys
Key life: 5,000,000 times
Working Distance: 5m
Requirement: Windows 2000/XP/Vista/7/8/10/11/12/13/14/15/16/17/18/19/20
Battery Requirement: AA*1 batteries



DK204 Chocolate KEYBOARD

- 2.4G Keyboard & Mouse
- Chocolate-design, Comfort touching
- Double Waterproof
- Non-Skid Stand
- HD UV Silkscreen Characters



USB HUB



DH302

USB 3.0 HUB
Maximum transfer speed: 5Gbps
Interface: Input (USB 3.0 A-type male) x1
Output: USB 3.0 A-type female x4
Electronic switch: NO
Hot-swap: Support

DH307

Material: Plastic shell-Nickel-plated plug
Data transfer: USB 3.0 5Gbps
Size: 1. USB 3.0-A (25.4 x 12.7 x 4.1) Male
Size 2. USB 3.0-A (25.4 x 12.7 x 4.1) Female
Cable length: 30cm



4 in 1
USB 3.0 HUB



Webcam

USB Camera 720P



IM0225B

Resolution: 1280*720p
Master chip: Sony
High definition: 1.3 million pixels
Built-in microphone
Camera angle: 90-degree
Interface type: USB 2.0



IM0228A

Resolution: 1280*720p
Master chip: Realtek
High definition: 1.3 million pixels
Interface type: USB 2.0



IM0221A

Resolution: 1280*720p
Master chip: Realtek
Lens: 1.3 million pixels
Angle: 30-degree, external/360-degree
USB 3.0 + 3.5 mm headphone jack

USB Camera 1080P



IM0225

Resolution: 1920*1080p
Master chip: Sony
Video frame rate: 30FPS
Driver type: no driver (plug and play)
Interface type: USB 2.0
High definition: 2 million pixels



IM0228

Resolution: 1920*1080p
Master chip: Sony
Video frame rate: 30FPS
Driver type: no driver (plug and play)
Interface type: USB 2.0
Horizontal angle: 65-130°



IM0226

Resolution: 1920*1080p
Master chip: Sony
Video frame rate: 30FPS
Driver type: no driver (plug and play)
Interface type: USB 2.0
Wide angle: 65-130°



IM0185A

Resolution: 1920*1080p
Master chip: Sony + 0.5mm glass lenses
Hardware pixels: 1080P (2 million pixels)
Focus mode: Manual focus
Lens wide angle: 65°



IM0232

Resolution: 1920*1080p
Master chip: Sony
Hardware pixels: 1080P (2 million pixels)
Focus mode: Auto focus
Lens wide angle: 70°



IM0233

Resolution: 1920*1080p
Master chip: Sony
Hardware pixels: 1080P (2 million pixels)
Focus mode: Manual focus
Lens wide angle: 65°

Chargers

Wall Charger



M010
Input (Euro/US): 100-240V 50/60Hz
Output: 1*USB-Port 5V 1A



M013
Input (Euro/US): 100-240V
Output: 2*USB-Port 5V-2A



M011
Input (Euro/US): 100-240V 50/60Hz
Output: 1*USB-Port 5V 2A



M042
Input (Euro/US): 100-240V 50/60Hz
Output: 1*USB-Port 5V 2A



USB Desktop Charger



M040

Input/PSU:
AC 100-240V 50/60Hz 5 SA Max
Output/Quick Charge:
3.6V-6.5V 3A/5 5V-9V 2A/9V-12V 1.5A
Output/Smart Charge/Total: 5.4A Max



M044

Input: AC 100-240V 50/60Hz 1.5A Max
Output/Quick Charge: 5C 3.6V-6.5V 3A/5 5V-9V 2A/9V-12V 1.5A
Output/Smart Charge: 5.4A-10.2A Max



M045

Input: AC 100-240V 50/60Hz 1.3A/0.7A Max
Output/Smart Charge: 5V 4A / 9V 5A Max

Car Charger



M075

Input: DC 12-24V
Output: DC 5V-2.1A
Interface: USB-Port X2



M076

Input: DC 12-24V
Output: DC 5V-3.1A
Interface: USB-Port X2



HDMI Splitter



DD412A

HDMI Splitter 1*2/1.4V(3D)
1080P@60Hz, Metal case, Black



DD414A

HDMI Splitter 1*4/1.4V(3D)
1080P@60Hz, Metal case, Black



DD416A

HDMI Splitter 1*8/1.4V(3D)
1080P@60Hz, Metal case, Black



DD432

HDMI 2.0 Splitter 1x2
2.0V Support 4K@60Hz/YUV 4:4:4 HDCP 2.2,
Metal case, Black



DD424

HDMI 2.0 Splitter 1x4
2.0V Support 4K@60Hz/YUV 4:4:4 HDCP 2.2,
Metal case, Black



DD428

HDMI 2.0 Splitter 1x8
2.0V Support 4K@60Hz/YUV 4:4:4 HDCP 2.2,
Metal case, Black



HDMI Switch



DD432

HDMI Switch 2*1 ports 1.4V(3D)
1080P@60Hz, Metal case, Black



DD433

HDMI Switch 3*1 ports 1.4V(3D)
1080P@60Hz, Metal case, Black



DD434

HDMI Switch 4*1 ports 1.4V(3D)
1080P@60Hz, Metal case, Black



DD435

HDMI Switch 5*1 ports 1.4V(3D)
1080P@60Hz, Metal case, Black



DD463

HDMI 2.0 Switcher 3x1
2.0V Support 4K@60Hz/YUV 4:4:4 HDCP 2.2,
Metal case, Black



DD465

HDMI 2.0 Switcher 5x1
2.0V Support 4K@60Hz/YUV 4:4:4 HDCP 2.2,
Metal case, Black

KVM Switch



DD225-4K

2 Port HDMI KVM Switch/1.4V, 4K@30Hz, Plastic case

Version: HDMI 1.4
Switching Mode: External Button
Input: HDMI x2 (in)
HDMI Output: USB-AF x2 (DP+Button)
Resolution: 4K@30Hz, 1.2m



DD211-2K

2 Port VGA KVM Switch/1080P@60Hz, Plastic case

Version: VGA
Switching Mode: External Button
Input: VGA x2 (in)
HDMI Output: USB-AF x2 (VGA+Button)
Resolution: 1080P@60Hz, 1.2m



DD251-4K

2 Port DP KVM Switch/1.4V, 4K@60Hz, Plastic case

Version: DP 1.2
Switching Mode: External Button
Input: DP x2 (in)
HDMI Output: USB-AF x2 (DP+Button)
Resolution: 4K@60Hz, 1.2m



DD241-4K

2 Port DVI KVM Switch/4K@30Hz, Plastic case

Version: DVI
Switching Mode: External Button
Input: DVI-D x2 (in)
HDMI Output: USB-AF x2 (DVI+Button)
Resolution: 4K@30Hz, 1.2m



DD222

**HDMI KVM Switch/2*1
1.4V/1080P@60Hz Metal case Black**



DD224

**HDMI KVM Switch/4*1
1.4V/1080P@60Hz Metal case Black**

VGA Splitter



DD132

**VGA Splitter/1*2
330MHz Metal case Black**



DD134

**VGA Splitter/1*4
330MHz Metal case Black**



DD138

**VGA Splitter/1*8
330MHz Metal case Black**

Extender



DD471

**HDMI RJ45 Extender
Support 4K@30Hz length up to 50m,
Metal case Black**



DD473

**HDMI Fiber Optic Extender
(Uncompressed)
Support Max Resolution 4K@60Hz
Transmission distance: standard 2km(Uncompressed),
maximum 30km, Black Metal case**



DD474

**HDMI Fiber Optic Extender
Support Max Resolution 1080P@60Hz
Transmission distance: standard 20km
(Uncompressed), maximum 30km,
Black Metal case**



DD181

**VGA RJ45 Cat5e/6
Extender
length up to 100m Metal case,
Black**



DD182

**VGA Fiber Optic Extender
Support Max Resolution 1080P@60Hz
Transmission distance: standard 20km
(Uncompressed), maximum 30km,
Black Metal case**

**VCOM**

AV Adaptor



CORE VALUE OF VCOM BRAND

Brand target to be the global NO.1 brand in
computer peripherals
Brand character: user value
Steps: Beyond your imagination
Brand positioning: one-stop supplier for global
computer peripherals
Service: providing an online consultation and
educational service

DISTRIBUTE VCOM BRAND PRODUCTS

VCOM is a rapid developing and we have distributors
agents in 80 countries up to now. We would like to work
with you to develop your local market, move forward
together to a brilliant prospect. Contact us now!
vcom@vcom.hk

**VCOM**

AV Adaptor

